

(12) UK Patent Application (19) GB (11) 2 277 990 (13) A

(43) Date of Printing by UK Office 16.11.1994

(21) Application No 9401813.2

(22) Date of Filing 06.08.1992

(30) Priority Data

(31) 913182 (32) 15.08.1991 (33) NO

(86) International Application Data

PCT/NO92/00127 No 06.08.1992

(87) International Publication Data

WO93/04366 En 04.03.1993

(51) INT CL⁵

G01N 30/46 33/18

(52) UK CL (Edition M)

G1B BCD

U1S S1271 S1434

(56) Documents Cited by ISA

DE 004006689 A1 DE 003641645 A1 DE 003119187 A1

(58) Field of Search by ISA

INT CL⁵ G01N 30/46 33/18

(71) Applicant(s)

Bjorn Dybdahl

Lillesund Terrasse 4D, N-5500 Haugesund, Norway

(74) Agent and/or Address for Service

Stevens, Hewlett & Perkins

1 Serjeant's Inn, Fleet Street, LONDON, EC4Y 1LL,


United Kingdom

(72) Inventor(s)

Bjorn Dybdahl

(54) Liquide sample analyser

(57) The invention relates to a liquid sample analyser for analysing water samples with regard to their content of elements/metals and/or chlorides and/or sulphate, preferably in connection with the determination of electrical conductivity and/or degree of acidity, comprising at least one mobile phase container (1a - 1c) for reagent agent(s) and means (3a - 3c) for causing said reagent agent(s) to flow in a pipeline circuit together with said liquid sample, and possibly including means (7, 15; 8, 14) for the determination of the electrical conductivity and the degree of acidity of the liquid sample, respectively. Determination of the desired liquid sample parameters are achieved under the same conditions on one liquid sample injection into the analyser. To this end, the liquid sample analyser is based on ion chromatography and comprises ion separating column means (10a - 10c), pipeline and valve means (6, 6'; 5a - 5c) for the supply of liquid sample into the system on one injection (at 20), said valve means (5a - 5c), said ion separating column means (10a - 10c) and, possibly, sensor means (7; 8) associated to the measurement of conductivity and degree of acidity are enclosed within a cabinet or furnace casing (18), in order to maintain the same conditions for those operations performed by the components (5a - 5c, 9a - 9c, 10a - 10c, 7, 8, 11) enclosed within said casing (18).



GB 2 277 990 A